



Transmissometer Model 8400



- Innovative Dirty Window Control
- Precise Automated Alignment
- Minimal Maintenance Required
- Built Tough and Durable

OVERVIEW

Visibility and Runway Visual Range are the most important meteorological quantities in aviation safety. At times of reduced visibility, the accurate and reliable determination of Runway Visual Range (RVR) from visibility is crucial to maximise air traffic capacity without compromising safety. Transmissometers provide accurate and reliable solutions for automatic measurement of RVR. As the sampled air volume is rather large – typically over a 30m baseline – the accuracy of the measurement is high and stable. The Model 8400 represents a new generation of transmissometers. It's extremely accurate, can be installed by a single person, and requires significantly less frequent maintenance.

The Model 8400 has an improved alignment system, a revolutionary window contamination control solution, and it uses the latest high-quality semiconductors to guarantee the accuracy, stability, and robustness of the system.

INNOVATIVE WINDOW CLEANING

The transmitter and receiver heads use an innovative window design, with the protective outside window built as a rotating disc of glass. When the computer detects that one of the 6 sections of glass has become contaminated, a new piece of clean glass is automatically rotated into place. The solution includes a new, patented "in-line" contamination detection technique that directly

measures and compensates for window contamination until a clean section of glass is needed. This way, operation is practically maintenance free for long periods of time. When the entire disc is dirty, it can be replaced with a clean disk in seconds and the contaminated disc can be taken back to the workshop for cleaning.

ICAO ALGORITHMS

Luminance values together with the integrated runway light intensity value are used to calculate RVR using official WMO/ICAO algorithms. The accuracy requirements meet or exceed the recommendations of ICAO Annex 3 for the entire range of RVR in airport operations, ranging from CAT I to CAT IIIC.

SENSORS

SPECIFICATIONS

Parameter	Specification
MOR Ranges	10 - 10,000 m
Transmittance Range	0 - 100% Transmittance
Reporting Resolution	0.005%
Accuracy	According to ICAO and WMO specifications for RVR & visibility
Averaging Period	60 seconds
Lamp Transmitter Source	Xenon Flash Lamp
Measurement Principle	Pulsed Xenon transmitters and receivers measure transmissivity of the atmosphere
Lamp Life	Greater than 20,000 hours
Baseline	15m, 30m, 50m or 75m
Dual Baseline	15m + 50m or 15m + 75m
Communications	RS232, RS422, FSK modem, fiberoptic mode, radio modem, ethernet
Power Supply	115 / 130 / 230 / 240 VAC 50 - 60 Hz
Power Consumption	500W with heaters, per unit
Background Luminance	
Measuring Range	0 to 40,000 cd/m ²
Accuracy	+/- 7%
Viewing Angle	10°
Environmental Conditions	
Temperature Range	-40°C to +60°C
Humidity Range	0 to 100% RH
Wind Speed	Up to 75 m/s
Mounted Height	2.5 m

ORDERING INFORMATION

Part Number	Description
8400	Transmissometer
8400-DB	Transmissometer - Dual Baseline
8400-ALS	Ambient Light Sensor



CE CERTIFIED


All Weather Inc.
 1165 National Dr.
 Sacramento, CA 95834
allweatherinc www.allweatherinc.com

Phone: 916-928-1000
 USA Toll Free: 800-824-5873
 Fax: 916-928-1165

Rev. A 4/2014