



Temp/Humidity Probe Model 5190



Overview

The Model 5190-F Temperature/Humidity Probe is designed for a variety of environmental monitoring applications, including All Weather Inc.'s Automated Weather Observing Systems (AWOS). The 5190-F operates with a DC supply voltage and has a low current draw. Relative humidity is measured with a thin-film capacitor sensor, and temperature is measured using a Pt100 RTD with an accuracy of $\pm 0.1^{\circ}\text{C}$. The signals from the sensors are converted into two linearized output voltages.

Parameter	Output Voltage	Range
RH	0–1.0 V DC	0–100% RH
Temperature	0–1.0 V DC	-40°C to +60°C

The Model 5190-F probe is Federal Aviation Administration (FAA) certified, meeting all of the most current regulatory requirements.

SENSORS

SPECIFICATIONS

Parameter	Specification
Humidity Sensor	Thin-Film Capacitor
Temperature Sensor	Pt100 RTD
Operating Temperature Limits	-40°C to +60°C
Humidity Output Signal (Linear)	0-1.0 V DC = 0-100% RH
Temperature Output Signal (Linear)	0-1.0 V DC = -40°C to +60°C
Minimum Load per Output	10 kΩ
Accuracy (at 23°C)	±1.5% RH ±0.1°C
First Signal After	2.3 s
Measurement Interval	0.7 s
Supply Voltage	5-24 V DC
Current Consumption	approx. 4 mA
Cable Length	5 m (16 ft), tinned ends
Sensor Protection	Wire mesh filter

ORDERING INFORMATION

Part Number	Description
5190-F	Temperture and Humidity Probe
8190	Motor Aspirated Radiation Shield

DIMENSIONS & WEIGHTS

Size	8.19" x 0.59" diameter (208 mm x 15 mm diameter)
Weight	0.27 lb (120 g)
Shipping Dimensions	8" x 10" x 2" (203 mm x 254 mm x 51 mm)
Shipping Weight	1 lb (454 g)



All Weather Inc.

www.allweatherinc.com

Phone: 916-928-1000
USA Toll Free: 800-824-5873
Fax: 916-928-1165

Rev. C 05/2019